# Interior installation

## **Rail systems**

## TS punched rail 18 x 38 mm

Simply locate and secure with a screw. The location system makes assembly and dismantling easier. It only needs to be secured on one side, but may be secured on both sides if required.

## Installation options:

- On the vertical TS, SE enclosure section
   On the outer mounting level
- On the horizontal TS, SE enclosure section
- On base configuration rail for CM

#### Material: - Sheet steel

Surface finish: - Zinc-plated

## Supply includes:

Assembly screws

## Note:

 In enclosures with a mounting plate, 2 punched rails are already included with the supply

For enclosure width/depth mm	Packs of	Model No.
400	4 pc(s).	8612.240
500	4 pc(s).	8612.250
600	4 pc(s).	8612.260
800	4 pc(s).	8612.280

## + Accessories:


- Screws, see page 625Cable tie for fast assembly 2597.000,
- see page 667
- Cable clamps, see page 666

### **Configuration examples:** See from page 598









## **TS** support strips

- Installation options: On the vertical and horizontal TS, SE enclosure
- section
   On the outer mounting level, all-round, at the
- same height
  On the inner mounting level, all-round, heightoffset
- On the tubular door frame TS, SE
- On the perforated door strip CM, TP

## Material:

#### - Sheet steel

Surface finish:

## Zinc-plated

## Supply includes:

Assembly screws

#### For the outer mounting level

Length mm	Packs of	Model No.				
340	20 pc(s).	4694.000				
440	20 pc(s).	4695.000				
540	20 pc(s).	4696.000				
740	20 pc(s).	4697.000				
	mm 340 440 540	mm         Packs of           340         20 pc(s).           440         20 pc(s).           540         20 pc(s).				

## Accessories:

- Screws, see page 625
- Cable tie for fast assembly 2597.000, see page 667

## Configuration examples:

See from page 598

#### For the inner mounting level and for mounting on doors

For enclosure width/depth mm	For door width mm	Length mm	Packs of	Model No.
-	400	290	20 pc(s).	4594.000
400	500	390	20 pc(s).	4309.000
500	600	490	20 pc(s).	4596.000
600	-	590	20 pc(s).	8800.130
-	800	690	20 pc(s).	4598.000
800	900	790	20 pc(s).	4579.000
-	1000	890	20 pc(s).	4599.000



